

## N630 Outdoor IP camera with megapixel resolution




- Meets IP66 standard for dust and water protection
- Day/Night mode and motorized IR cut filter
- IR Illumination with working distance up to 15 meters
- 30 fps at 720p HD resolution
- Simultaneous motions: H.264/MPEG-4/MJPEG
- WDR-mode support (Wide Dynamic Range)
- Network-attached storage (NAS) recording
- 16-channel software included
- MicroSDHC memory card support
- PoE technology support

N630 IS AN OUTDOOR MEGAPIXEL IP CAMERA WITH IR ILLUMINATION AND DAY/NIGHT MODE. IT ALLOWS TO INSTALL TWENTY-FOUR-HOUR VIDEO SURVEILLANCE SYSTEMS WITH HIGHER IMAGE REQUIREMENTS.





	GENERAL FEATURES		system log to a shared folder or
Model	N630		to NAS - continually, by alarm,
Image sensor	OmniVision, 1/4" CMOS, Day/Night mode		by schedule, periodically
ago concor	Progressive scan	Memory card	Images, video data, system log:
Sensor dimensions	3.88x2.43 mm	recording	continually, by alarm, by schedule,
Sensitivity	0.2 lux / 0.02 lux (DSS @ 2 fps)	l	periodically
Illumination	IR LEDs (850 nm), 3 pcs, up to 15 m	FTP uploading	Images, video data, system log:
IR filter	Motorized IR cut filter	i ii upiouuiiig	by alarm, by schedule, periodically
Shutter time	1/2 - 1/10000 s		(pre-,post recording, time span: 1 min. to 24 h.)
AGC	1x to 64x	Sending by e-mail	Images, video data, system log:
Extra	WDR (8 levels), Noise Reduction, BLC	50ag 2) 0a	by alarm, by schedule, periodically
LENS			(pre-,post recording, time span: 1 min. to 24 h.)
Type	M12, F1.8		CONNECTORS
Focal length	4.0 mm	Ports/Connectors	RJ-45 for Ethernet 10/100 Base-T,
Angle of view	52° (horizontal)	1 0110/001111001010	power connector, memory card slot,
Aligio of view	VIDEO		Reset button,
Video streaming	H.264 Baseline Profile, MPEG-4 Simple Profile		Video out (BNC connector)
video su earning	Motion JPEG (simultaneous encoding),	Memory card	MicroSD/MicroSDHC (up to 32 GB)
	unicast and multicast support	Wellioly Card	CONTROL/SETTINGS
Resolutions	1280x800, 1280x720, 640x480,	Control	Professional 16-channel software for
nesolutions	320x240, 160x120	Control	recording and monitoring, software for
Eromo roto	H.264/MPEG-4/Motion JPEG:		searching and setting of IP cameras (included)
Frame rate			
Dit wata	up to 30 fps at all resolutions	LIDaD	Firefox, Safari, IE 9.0 or later
Bit rate	H.264/MPEG-4: customize settings,	UPnP	Windows UPnP auto-discovery
	presets (5 fixed),		(XP SP3/Vista/Windows 7)
	fixed bit rate:	D	OPERATION
	from 32 kbit/s to 6 Mbit/s;	Power	12 V DC; PoE IEEE 802.3 af
D£1-	Motion JPEG: customize settings, presets	From power supply	2.6 W (without IR illumination)
Profile	10 profiles, individual adjustment	F D . F	5.6 W (with IR illumination)
View areas	Up to 4 view areas	From PoE	4 W (without IR illumination)
Image settings	Brightness, contrast, saturation, sharpness	150	7.7 W (with IR illumination)
	Rotation: mirror, flip,	LED	Power, network status
	mirror+flip; time/date, text	Operating temperature	От -40 до +50°C
_	Privacy Zone Masking	Waterproof	IP66
Zoom	Digital 10x (on/off)	Dimensions	Ø69×280 mm
	NETWORK	Net Weight	780 g
Interfaces	10Base-T/100Base-T Ethernet port	Casing	Metal
Supported protocols	TCP/IP, DHCP, PPPoE, ARP, ICMP, FTP,	MINIMUM REQUIREMENTS	
	SMTP, DDNS, NTP, UPnP, Bonjour, RTSP,	Network interface card	Yes
	RTP, HTTP, HTTPS, UDP, ONVIF v2.2	Browser	Internet Explorer 9.0 or later
Security	Multilevel users access	Operating system	Windows XP, Vista, Windows 7,
	with password protection		MAC OS Leopard 10.5 or later
	(up to 5 simultaneous connections),	Processor	2.8 GHz Pentium 4 or equivalent AMD
	HTTPS encryption, IP Filter	RAM	1 GB (recommended 2 GB or higher)
Connection	DHCP, static IP address	Video card	256 Mb
	RECORDING AND EVENTS		PACKAGE CONTENTS
Events	Multizone motion detection	Package contents	IP-camera (lens and bracket pre-installed)
	with sensitivity and threshold adjustment,		RJ45 connector, mounting kit
	network link down, IR filter,		Sunshield
	boot device, periodical event,		12 V, 1 A DC power supply
	IP-notification, capacity warning,		Quick installation guide
	tampering detection		CD with software and user's manuals
	Recording of video data, images,		OD WITH SOFTWARD AND GOOD S MAINGAID





Important! Purchasing a product please check its package content and inspect it for mechanical damages.

Product specifications can be changed without preliminary notice.