


N37210

An outdoor IP camera with two megapixel resolution




- Progressive scan CMOS
- 30 fps at 1920x1080 resolution
- Day/Night mode and motorized IR cut filter
- IR illumination with up to 35 meters of working distance
- Meets IP66 standard for dust and water protection
- Built-in heater and fan
- Simultaneous encoding of H.264/MPEG-4/Motion JPEG
- WDR-mode support (Wide Dynamic Range)
- Network-attached storage (NAS) recording
- 16-channel software included
- MicroSDHC memory card support

N37210 IS AN OUTDOOR TWO-MEGAPIXEL IP CAMERA WITH X-PANNER FUNCTION FROM BEWARD, WHICH ALLOWS SPECIFYING AND USING 4 SEPARATE VIEW AREAS WITH INDIVIDUAL PROFILE PARAMETERS FOR EACH AREA.



- 1 - MicroSD slot
- 2 - Video out
- 3 - Power connector
- 4 - Terminal connector
- 5 - Reset button
- 6 - NTSC/PAL switch
- 7 - Network connector





- 8 - Lens
- 9 - IR LED
- 10 - Light sensor

| GENERAL FEATURES | | | |
|-----------------------------|--|-----------------------------|---|
| Model | N37210 | NAS recording | Recording of video data, images, system log to a shared folder or to NAS - continually, by alarm, by schedule, periodically |
| Image sensor | OmniVision, 1/2.7" CMOS, Day/Night mode Progressive scan | FTP uploading | Images, video data, system log: by alarm, by schedule, periodically (pre-, post recording, time span: 1 min. to 24 h.) |
| Sensor dimensions | 5.85x3.27 mm | Memory card recording | Images, video data, system log: continually, by alarm, by schedule |
| Sensitivity | 0.05 lux (Day) / 0.01 lux (Night) 0.007 lux (DSS @ 2 fps) | CONNECTORS | |
| Illumination | IR LEDs (850 nm), 4 pcs., up to 35 m | Ports/Connectors | RJ-45, terminal block for power supply, memory card slot, Reset button, video out (RCA connector). Terminal block for 2 digital input/output and audio input/output, PAL /NTSCswitch |
| IR filter | Motorized IR cut filter | Digital I/O | 2 input/2 output (max. 30 V), NO/NC mode |
| Shutter time | 1/2 - 1/10000 sec | Memory card | MicroSD/MicroSDHC (up to 32 GB) |
| AGC | 1x to 64x | CONTROL/SETTINGS | |
| Extra | WDR (8 levels), Noise Reduction, BLC | Control | Professional 16-channel software for recording and monitoring, software for searching and setting of IP cameras (included) |
| LENS | | UPnP | Windows UPnP auto-discovery (XP SP3/Vista/Windows 7) |
| Type | Varifocal, auto iris, F1.2, 3.0-9.0 mm | OPERATION | |
| Angle of view | 36-110° (horizontal) | Power | 12 V DC, 1.2 A, 14 W max. PoE 802.3af |
| VIDEO | | Power from PSU* | 3.9 W (heater and fan only) 7.9 W (IR illumination only (max.)) 9.6 W (IR illumination (max.) and heater) 8.87 W (IR illumination (max.) and fan) |
| Video streaming | H.264 Baseline Profile, MPEG-4 Simple Profile, Motion JPEG (simultaneous encoding) | Power from PoE** | 3.9 W (heater and fan only) 7.9 W (IR illumination only (max.)) |
| Resolution | 1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 640x480, 320x240 | Heater and fan | Built-in, auto turn on/off Heater activates at temperatures below +5°C Fan activates at temperatures above +50°C |
| Frame rate | H.264/MPEG-4/Motion JPEG: up to 30 fps at all resolutions | LED | Power, network/memory card status |
| Bit rate | H.264/MPEG-4: customize settings, presets (5 fixed), fixed bit rate: from 32 kbit/s to 10 Mbit/s; Motion JPEG: customize settings, presets | Operating temperature | -65 to +50°C, IP66 |
| Profile | 10 profiles, individual adjustment | Dimensions | 360x125x250 mm (assembled) |
| Viewing areas | Up to 4 viewing areas | Net Weight | 1830 g |
| Image settings | Brightness, contrast, saturation, sharpness Rotation: mirror, flip, mirror+flip, time/date, text; Privacy Zone Masking | Casing | Metal |
| Zoom | Digital 10x (on/off) | MINIMUM REQUIREMENTS | |
| AUDIO | | Browser | Safari, Firefox, IE 9.0 or later |
| Audio input/output | 1 audio line input / 1 line output, gain | OS | Windows XP, Windows 7, MAC OS X |
| Compression | G.711 u-law, a-law, AMR | Processor, RAM | 2.8GHz P4 or equivalent AMD, 1GB |
| Extra | Full-duplex, half-duplex, simplex | Network interface card | Yes |
| NETWORK | | PACKAGE CONTENTS | |
| Interfaces | 10Base-T/100Base-T Ethernet port | Package contents | IP camera (lens pre-installed), Bracket mounting template, bracket with holder Gasket M25x1.5, sunshield, desiccant Mounting kit (with 2 keys), 2 terminal blocks Quick installation guide, CD with software and user's manuals Package |
| Supported protocols | TCP/IP, DHCP, PPPoE, ARP, ICMP, FTP, SMTP, DDNS, NTP, UPnP, Bonjour, RTSP, RTP, HTTP, HTTPS, UDP, ONVIF v2.2 | | |
| Security | Multilevel users access with password protection (up to 5 simultaneous connections), HTTPS encryption, IP Filter | | |
| Connection | DHCP, static address | | |
| RECORDING AND EVENTS | | | |
| Events | Audio detection, multizone motion detection with sensitivity and threshold adjustment, capacity warning, boot device, digital input, network link down, IP-notification, periodical event, tampering detection | | |
| Sending by e-mail | Images, video data, system log: by alarm, by schedule, periodically (pre-, post recording, time span: 1 min. to 24 h.) | | |

* It is possible to use IR illumination, heater and fan together while using power supply unit.

** When using PoE, heater and fan turn off if IR illumination is enabled.



Important! When purchasing this product, please check its package content and inspect it for mechanical damages. Product specifications can be changed without preliminary notice.